


Info generali**Esterno - Lampade da terra**

Outdoor floor, wall or ceiling mounted adjustable projector with double cable glands for in-out connection, integrated LED sources and direct light emission



Ean	8021696325019
Articolo	O-ZONE PT SMALL
Installazione	Lampade da terra
Garanzia	5 years
Peso lordo	1.1 kg
Volume	0.006032 m ³

Info tecniche e installative

Peso netto	0.8 kg
Classe di isolamento	I
Grado di protezione	IP66
Conformità	CE
Temperatura d'esercizio	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	LED 13 W
Emissione	Direct
Consumo massimo	max 13 W
Caratteristiche LED	LED COB CITIZEN
CCT LED	3000 K
Durata LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	47°
Flusso sorgente	1150 lm
Flusso utile	970 lm
Rischio fotobiologico	1