

Info generali

Esterno - Proiettori Esterno


Outdoor floor, ceiling or wall-mounted adjustable projector with integrated LED sources and direct light emission



Ean	8021696261294
Articolo	ULEX PR H20 SOURCE
Installazione	Proiettori Esterno
Garanzia	5 years
Peso lordo	1.36 kg
Volume	0.0042 m ³

Info tecniche e installative

Peso netto	1.19 kg
Classe di isolamento	I
Grado di protezione	IP65
Conformità	CE
Temperatura d'esercizio	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	In-built, included Replaceable (by qualified operators only), electronic
Resistenza al carico	IK06
Accessori non inclusi	Glare shielding cover, Base for external connection, Ground fixing spike



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	No
Potenza	15 W
Emissione	Direct
Consumo massimo	max 15 W
Caratteristiche LED	LED SMD OSRAM
CCT LED	3000 K
Durata LED (t. 25°c)	50000 h
CRI	> 80
Fascio luminoso	30°
Flusso sorgente	1280 lm
Flusso utile	980 lm