

Info generali

Esterno - Proiettori Esterno


Outdoor floor, ceiling or wall-mounted adjustable projector with direct light emission



Ean	8021696245041
Articolo	STARLIGHT PR 05.5W 4000K
Installazione	Proiettori Esterno
Garanzia	5 years
Peso lordo	0.35 kg
Volume	0.00045 m³

Info tecniche e installative

Peso netto	0.28 kg
Classe di isolamento	III
Grado di protezione	IP68
Conformità	CE
Temperatura d'esercizio	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	24 V DC
Alimentatore	Required, remoted, not included
Resistenza al carico	IK07
Accessori non inclusi	Glare shielding cover, Waterproof connection, Ground fixing spike, Remote on-off driver



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	5,5 W
Emissione	Direct
Consumo massimo	max 5,5 W
Caratteristiche LED	LED COB CITIZEN / BRIDGEL
CCT LED	4000 K
Durata LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Fascio luminoso	30°
Flusso sorgente	670 lm
Flusso utile	580 lm
Rischio fotobiologico	1