

Info generali

Esterno - Proiettori Esterno


Outdoor floor, ceiling or wall-mounted adjustable projector with direct light emission



Ean	8021696248387
Articolo	STARLIGHT PR 10.0W 3000K
Installazione	Proiettori Esterno
Garanzia	5 years
Peso lordo	1.23 kg
Volume	0.00144 m³

Info tecniche e installative

Peso netto	0.95 kg
Classe di isolamento	III
Grado di protezione	IP68
Conformità	CE
Temperatura d'esercizio	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	24 V DC
Alimentatore	Required, remoted, not included
Resistenza al carico	IK07
Accessori non inclusi	Glare shielding cover, Waterproof connection, Ground fixing spike, Remote on-off driver



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	10 W
Emissione	Direct
Consumo massimo	max 10 W
Caratteristiche LED	LED COB BRIDGELUX
CCT LED	3000 K
Durata LED (t. 25°c)	50000 h
CRI	> 80
SDCM	3
Fascio luminoso	30°
Flusso sorgente	1000 lm
Flusso utile	840 lm
Rischio fotobiologico	1