

## Info generali

## Lampadine e accessori - Strip led

Indoor dimmable LED strip with integrated LED sources and direct light emission



|                      |                                                                             |
|----------------------|-----------------------------------------------------------------------------|
| <b>Ean</b>           | 8021696346489                                                               |
| <b>Articolo</b>      | STRIP LED 240 SMD 15W/M 3000K CRI90 IP20                                    |
| <b>Installazione</b> | Slot / Tesi 20 mm / Vision profile - max length for connection in line: 5 m |
| <b>Garanzia</b>      | 5 years                                                                     |
| <b>Peso lordo</b>    | 0.11 kg                                                                     |
| <b>Volume</b>        | 0.000365 m <sup>3</sup>                                                     |

## Info tecniche e installative

|                              |                                 |
|------------------------------|---------------------------------|
| <b>Peso netto</b>            | 0.08 kg                         |
| <b>Classe di isolamento</b>  | 3                               |
| <b>Conformità</b>            | CE                              |
| <b>Alimentazione</b>         | 24 V DC                         |
| <b>Dimmer</b>                | 1, Phase-cut                    |
| <b>Alimentatore</b>          | Required, remoted, not included |
| <b>Grado di protezione</b>   | 20                              |
| <b>Lunghezza fornita</b>     | L 5000 x H 1 x P 5 mm           |
| <b>Accessori non inclusi</b> | Remote driver                   |

## Info sorgente e prestazionali

|                              |                |
|------------------------------|----------------|
| <b>Potenza</b>               | 75 W           |
| <b>Emissione</b>             | Direct         |
| <b>Consumo massimo</b>       | max (1 m) 15 W |
| <b>CCT LED</b>               | 3000 K         |
| <b>Durata LED (t. 25°C)</b>  | 50000 h        |
| <b>CRI</b>                   | > 90           |
| <b>SDCM</b>                  | 3              |
| <b>Fascio luminoso</b>       | 120 °          |
| <b>Flusso utile</b>          | (1 m) 1450 lm  |
| <b>Rischio fotobiologico</b> | 1              |